

# **Aluminum MultiView Doors**

Amarr<sup>®</sup> 3582



Amarr 3582 Aluminum MultiView doors make a unique design statement with the widest single piece of glass that specifications, safety, and reliability standards allow. Constructed of 2" thick extruded aluminum rails and stiles, these doors are built to last. The ClearView Aluminum Strut System provides strength and durability without restricting the viewing area. With a wide selection of glass, acrylic and polycarbonate glazing options, in more than two dozen paint and anodize finishes, the Amarr 3582 is a distinctive choice for any building where style and functionality are important.



#### CONSTRUCTION

### Amarr 3582

MultiView Aluminum door

- · 2" thick extruded aluminum rails & stiles
- Tongue and groove section joints provide additional protection against the elements
- · Equal glass heights in all sections of a door
- · Glass expanses up to 8'2" wide



Track: All Amarr doors are available with both 2"or 3" track in Standard Lift, High Lift, Vertical Lift, Low Headroom, and Follow the Roof Pitch. Custom track configurations are also available. For drawings and more information, please

Springs: Torsion springs are oil tempered, helical wound and custom computed for each door for a minimum 10,000 cycle life. Optional springs are available up to 100,000 cycle life.

Standard Hardware: Galvanized steel hinges and track brackets. All rollers have minimum 10-ball bearings.

#### COLORS

# In Stock Finishes









WHITE Powder Coat (WH)

#### **SPECIFICATIONS**

Amarr	Amarr 3582
MATERIAL	Aluminum
CONSTRUCTION LAYERS	Single
DOOR THICKNESS	2" (5.1cm)
SECTION HEIGHTS <sup>1</sup>	Varies by door height
MINIMUM DOOR WIDTH	2' 0"
MAXIMUM DOOR WIDTH	20' 2" (in 1"increments)
MINIMUM DOOR HEIGHT <sup>1</sup>	6· 0 <del>-</del>
MAXIMUM DOOR HEIGHT <sup>1</sup>	20' 1"
CLEARVIEW STRUT SYSTEM	Only required for doors ≥ 16'
WIND LOAD <sup>2</sup> AVAILABLE	NA
FINISH WARRANTY <sup>3</sup>	5 Years
WORKMANSHIP/HARDWARE WARRANTY <sup>3</sup>	1 Year
GLASS WARRANTY <sup>3</sup>	1 Year

<sup>&</sup>lt;sup>1</sup> For complete section and door height configuration charts, visit amarr.com or contact your local Amarr dealer.

#### Special Order Finishes

Longer lead time and price upcharge may apply.

Actual color may vary from samples shown.

#### ANODIZE







PAINT PVDF (Kynar®) & Powder Coat







IVORY





SANDSTONE





SIERRA TAN



DARK IVY



LIGHT SEAWOLF







BURNT SUN















# CHAMPAGNE PEARLT

#### **GLAZING OPTIONS**

					S	ingle Par	ie					Insu	lated
		Tem	pered		Lami- nated	Po	lycarbon	ate		Acrylic		Temp	pered
	3/16"	3/16" Low-E	1/4"	1/4" Low-E	1/4"	Single 1/8"	Single 1/4"	Tri-Wall 5/8"	1/8"	1/4"	1/2"	1/2"	1/2" Low-E
CLEAR	STD	•	•	•		•	•	•	•	•	•	•	•
OBSCURE	•												
GRAY	•											•	•
BRONZE	•							•				•	•
GREEN												•	•
FROST			•					•				•	
SNOW					•			•					
WHITEOUT					•								
BLACK ICE					•								





RAL and custom paint colors available.
Price upcharge and additional lead time apply.


TPVDF only.

	PVDF (Kynar*)	Powder Coat
FADE RESISTANT	++	+
CORROSION RESISTANT	++	+
UV RESISTANT	++	+
ABRASION RESISTANT	+	++
STANDARD COLORS	26	21
RAL/CUSTOM COLOR PRICE UPCHARGE	\$	\$\$
TOUCH-UP PAINT	Included	Not Included

<sup>1.866.366.4814</sup> 

## **DOOR CONFIGURATIONS**

1	For Single Pane Glazin	9
Door Width	# Center Stiles	# Windows/Section
Up to 8'2"	0	2
8' 3" - 16' 2"	1	4
16' 3" - 20' 2"	2	6



	For Insulated Glazing	
Door Width	# Center Stiles	# Windows/Section
Up to 10'2"	1	4
10'3" - 16'2"	2	6
16' 3" - 20' 2"	3	8

Up to 10°2" Wide – 2 Panels			
	_	=	
1/12" 2012" Mide / Depole			
16'3"-20'2" Wide – 4 Panels			
16'3"-20'2" Wide – 4 Panels			





 $<sup>^{2}\,</sup>$  It is your responsibility to make sure your garage door meets local building codes.

<sup>&</sup>lt;sup>3</sup> For complete warranty details, visit amarr.com or contact your local Amarr dealer.